Recovery unit VRR12L

Refrigerants: Category III	R-12, R-134a, R-401C, R-500
Refrigerants: Category IV	R-22, R-401A, R-401B, R-402B, R-407C, R-407D, R408A, R-409A, R-411A, R-411B, R-412A, R-502, R-509
Refrigerants: Category V	R-402A, R-404A, R-407A, R-410A, R-507
Power supply	230/50 V/Hz
Power	3/4 KM
Motor speed	1450 rpm
Maximum current draw	4 A
Compressor	Oil-less, air-cooled, piston style
Automatic safety shut-off	38,5/3850 bar/kPa (558 psi)
Recovery rate: Category III - Vapor / Liquid / Push/pull	0,20 / 1,60 / 4,60 kg/min

Recovery unit VRR12L

Recovery rate: Category IV - Vapor / Liquid / Push/pull	0,25 / 1,80 / 5,60 kg/min
Recovery rate: Category V - Vapor / Liquid / Push/pull	0,25 / 2,20 / 6,30 kg/min
Operating temperature	0 ÷ 40 ^{0}C
Dimensions	400 x 250 x 355 mm
Weight	13,0 kg

Pictures of some products may vary. Every effort has been made to ensure that the information contained in this catalog is correct. Due to constant technological development, we reserve the right to make changes without notice.

Recovery unit VRR12L

Refrigerant recovery unit is used for the recovery of refrigerant HFC and HCFC.

The main features:

- rapid recovery of refrigerant
- little handy recovery unit
- equipped with a high and low pressure gauge
- manual reset
- one knob for easy operation