

## Recovery unit VRR24M



Refrigerants: Category III	R-12, R-134a, R-401C, R-500, 1234yf
Refrigerants: Category IV	R-22, R-401A, R-401B, R-402B, R-407C, R-407D, R-408A, R-409A, R-411A, R-411B, R-412A, R-502, R-509
Refrigerants: Category V	R-402A, R-404A, R-407A, R-407B, R-410A, R-507, R32
Power supply	230/50 V/Hz
Power	1 HP
Motor speed	3000 RPM
Maximum current draw	5 A
Compressor	Oil-less, air-cooled, piston style
Automatic safety shut-off	38,5/3850 bar/kPa (558 psi)

## Recovery unit VRR24M

Recovery rate: Category III - Vapor / Liquid / Push/pull	0,40 / 3,30 / 7,50 kg/min
Recovery rate: Category IV - Vapor / Liquid / Push/pull	0,50 / 3,85 / 8,50 kg/min
Recovery rate: Category V - Vapor / Liquid / Push/pull	0,50 / 3,85 / 9,50 kg/min
Operating temperature	0 ÷ 40 °C
Dimensions	380 x 250 x 360 mm
Weight	10,0 kg

Pictures of some products may vary. Every effort has been made to ensure that the information contained in this catalog is correct. Due to constant technological development, we reserve the right to make changes without notice.

---

## Recovery unit VRR24M

---

Refrigerant recovery unit is used for the recovery of refrigerant HFC and HCFC.

The main features:

- rapid recovery of refrigerant
- brushless DC motor with a capacity of 1 HP
- digital display
- equipped with a high and low pressure gauge
- self-purge function
- one knob for easy operation
- two-piston compressor