

## VRR12L-OS-R32



|                                                                    |                                                                                       |
|--------------------------------------------------------------------|---------------------------------------------------------------------------------------|
| Refrigerant:<br>category III                                       | R-12,R-134a,R-401C,R-500,1234yf                                                       |
| Refrigerant:<br>category IV                                        | R-22,R-401A,R-401B,R-402B,R-407C,R-407D,R-408A,R-409A,R-411A,R-411B,R-412A,R-502,R509 |
| Refrigerant:<br>category V                                         | R-402A,R-404A,R-407B,R-410A,R-507,R-32                                                |
| Oil separator                                                      | yes                                                                                   |
| Power supply                                                       | 230 V / 50 Hz                                                                         |
| Motor                                                              | 0,75 KM / 0,55 kW                                                                     |
| Motor speed                                                        | 1450 rpm                                                                              |
| Maximal<br>current draw                                            | 4A                                                                                    |
| Compressor                                                         | Oil-less, Air-cooled, Piston-style                                                    |
| Automatic<br>safety Shut-off                                       | 38.5bar / 3850kPa(558psi)                                                             |
| Recovery rate :<br>category III -<br>vapor / liquid /<br>push/pull | 0,20 / 1,60 / 4,60 kg/min                                                             |
| Recovery rate :<br>category IV -<br>vapor / liquid /<br>push/pull  | 0,25 / 1,80 / 5,60 kg/min                                                             |

## VRR12L-OS-R32

|                                                                  |                                                              |
|------------------------------------------------------------------|--------------------------------------------------------------|
| Recovery rate :<br>category V -<br>vapor / liquid /<br>push/pull | 0,25 / 2,20 / 6,30 kg/min                                    |
| Operating<br>temperature                                         | 0 - 40 °C                                                    |
| Dimensions                                                       | 450 x 250 x 355mm                                            |
| Weight                                                           | 14.2 kg                                                      |
| Set                                                              | Shoulder strap, dry filter, 15 cm hose, ¼" x ¼", O.F.P. hose |

Pictures of some products may vary. Every effort has been made to ensure that the information contained in this catalog is correct. Due to constant technological development, we reserve the right to make changes without notice.

## VRR12L-OS-R32

Refrigerant recovery unit VALUE with oil separator is used for the recovery of refrigerant HFC and HCFC.

The main features:

- rapid recovery of refrigerant
- with oil separator
- little handy recovery unit
- equipped with a high and low pressure gauge
- manual reset
- one knob for easy operation

O.F.P. hose it is used for connection with cylinders overfill sensor.



## VRR12L-OS-R32

